



DIESTRA ULTRA HD 15W40

Heavy Duty Diesel Engine Oil

DESCRIPTION

Elube Diestra Ultra HD 15W40 is a premium heavy-duty multigrade diesel engine oil designed to meet the stringent requirements of high-performance, low-emission diesel engines, including those equipped with EGR (Exhaust Gas Recirculation) systems. Formulated with high-quality 100% virgin base oils and advanced additive technology, it meets the API CI-4 specification and provides excellent protection against wear, deposits, oxidation, and soot-related viscosity increase.

INTERNATIONAL STANDARDS

- API CI-4

KEY FEATURES & BENIFITS

- **API CI-4 Performance:** Enhanced wear and deposit protection for high-output diesel engines.
- **Enhanced Thermal Stability:** Resists oxidation and oil thickening at high temperatures, extending oil life.
- **Wear Protection:** Reduces friction and wear, extending transmission life.
- **Superior Shear Stability:** Maintains viscosity in severe operating conditions.
- **All-Season Performance:** 15W-40 viscosity grade ensures protection in both hot and cold seasons.

SPECIFICATIONS

Parameters	Unit	Test Method	Results
Appearance	-	Visual	C & B
Colour	-	ASTM D1500	L 2.5
Density at 15 °C	kg/m ³	ASTM D1298	886
Viscosity at 40 °C	CST	ASTM D445	99.8
Viscosity at 100 °C	CST	ASTM D445	13.9
Viscosity Index	-	ASTM D2270	136.37
Pour Point	°C	ASTM D97	-30
Flash Point	°C	ASTM D92	234
TBN	M KOH/gm Oil	ASTM D2896	10.97

PACK SIZES

208 L

20 L

3X5 L

12X1 L

STORAGE & HANDLING

Store in a cool, dry, and well-ventilated area away from direct sunlight, heat, and ignition sources. Keep containers tightly closed to prevent contamination and use clean equipment when handling. Follow proper industrial hygiene practices, including the use of protective gloves and eyewear to avoid skin and eye contact. Dispose of used oil and empty containers in accordance with local environmental regulations, and keep the product out of reach of children and unauthorized personnel.