



FLUIDMAX DIII MV

AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

Elube Fluidmax DIII MV is a high-performance, multi-purpose ATF formulated with 100% virgin base oil to meet the demands of modern automatic transmissions, torque converters, power shift transmissions, and power steering systems. It ensures smooth shifting, superior wear protection, and excellent oxidation stability. Suitable for vehicles requiring DEXRON III, it supports extended service life and optimal transmission performance under varying conditions.

INTERNATIONAL STANDARDS

- DEXRON III

KEY FEATURES & BENIFITS

- **Smooth Shifting:** Provides seamless gear changes under a wide range of temperatures.
- **Enhanced Thermal Stability:** Resists oxidation and oil thickening at high temperatures, extending oil life.
- **Wear Protection:** Reduces friction and wear, extending transmission life.
- **Oxidation Resistance:** Prevents sludge and varnish buildup for cleaner operation.
- **Seal Compatibility:** Maintains integrity of seals and gaskets to prevent leaks.

SPECIFICATIONS

Parameters	Unit	Test Method	Results
Appearance	-	Visual	C & B
Colour	-	ASTM D1500	RED
Density at 15 °C	kg/m ³	ASTM D1298	852
Viscosity at 40 °C	CST	ASTM D445	362.25
Viscosity at 100 °C	CST	ASTM D445	7.218
Viscosity Index	-	ASTM D2270	182
Pour Point	°C	ASTM D97	-42
Flash Point	°C	ASTM D92	210

PACK SIZES

208 L

20 L

4X4 L

12X1 L

STORAGE & HANDLING

Store in a cool, dry, and well-ventilated area away from direct sunlight, heat, and ignition sources. Keep containers tightly closed to prevent contamination and use clean equipment when handling. Follow proper industrial hygiene practices, including the use of protective gloves and eyewear to avoid skin and eye contact. Dispose of used oil and empty containers in accordance with local environmental regulations, and keep the product out of reach of children and unauthorized personnel.