



NAUTIX MARINE SAE 15W40

Lube Marine Oil for Highly Rated Diesel Engines

DESCRIPTION

Elube Nautix Marine 15W40 is a high performance marine-grade diesel engine oil designed for superior protection in harsh marine conditions. Suitable for both naturally aspirated and turbocharged engines, it ensures excellent wear protection, corrosion resistance and thermal stability. Ideal for fishing vessels, cargo ships, patrol boats and onboard generators.

INTERNATIONAL STANDARDS

- API CI-4

KEY FEATURES & BENIFITS

- **API CI-4 Performance:** Enhanced wear and deposit protection for high-output diesel engines.
- **Enhanced Thermal Stability:** Resists oxidation and oil thickening at high temperatures, extending oil life.
- **Wear Protection:** Reduces friction and wear, extending transmission life.
- **Superior Shear Stability:** Maintains viscosity in severe operating conditions.
- **Performance:** The product is also very water resistant, with outstanding demulsibility capacity, enabling rapid removal of water after an ingress and the maintenance of good engine performance.

SPECIFICATIONS

Parameters	Unit	Test Method	Results
Appearance	-	Visual	C & B
Colour	-	ASTM D1500	L 2.5
Density at 15 °C	kg/m ³	ASTM D1298	895
Viscosity at 40 °C	CST	ASTM D445	108
Viscosity at 100 °C	CST	ASTM D445	13.21
Viscosity Index	-	ASTM D2270	136.37
Pour Point	°C	ASTM D97	-18
Flash Point	°C	ASTM D92	>=220
TBN	M KOH/gm Oil	ASTM D2896	14

PACK SIZES

208 L

20 L

STORAGE & HANDLING

Store in a cool, dry, and well-ventilated area away from direct sunlight, heat, and ignition sources. Keep containers tightly closed to prevent contamination and use clean equipment when handling. Follow proper industrial hygiene practices, including the use of protective gloves and eyewear to avoid skin and eye contact. Dispose of used oil and empty containers in accordance with local environmental regulations, and keep the product out of reach of children and unauthorized personnel.