PETROL ENGINE OIL-FULLY SYNTHETIC

DESCRIPTION

Elube Vellon E30 5W30 is a premium, high-performance multigrade motor oil formulated with 100% virgin base stock and advanced additives to protect modern gasoline and diesel engines. Suitable for Japanese, European, and Korean vehicles, it provides superior protection against wear, deposits, sludge, and oxidation. This oil ensures long engine life and enhanced performance across a wide range of operating conditions and temperatures.

INTERNATIONAL STANDARDS

API SP

KEY FEATURES & BENIFITS

- Outstanding Wear Protection: Advanced additives provide a strong lubricating film that reduces metal-to-metal contact.
- Enhanced Fuel Economy: Low viscosity improves engine efficiency and reduces fuel.
- Thermal Stability: Maintains performance at high temperatures.
- Low Temperature Performance: Superior flow and pump ability at cold temperatures for easier starts and reduced engine wear.
- Extended Drain Intervals: Long-lasting protection.

SPECIFICATIONS

Parameters	Unit	Test Method	Results
Appearance	-	Visual	C & B
Colour	-	ASTM D1500	L 2.5
Density at 15 °C	kg/m ³	ASTM D1298	852
Viscosity at 40 °C	CST	ASTM D445	61.2
Viscosity at 100 °C	CST	ASTM D445	11.1
Viscosity Index	-	ASTM D2270	173
Pour Point	°C	ASTM D97	-42
Flash Point	°C	ASTM D92	227

PACK SIZES

208 L

4X4 L

12X1 L

STORAGE & HANDLING

Store in a cool, dry, and well-ventilated area away from direct sunlight, heat, and ignition sources. Keep containers tightly closed to prevent contamination and use clean equipment when handling. Follow proper industrial hygiene practices, including the use of protective gloves and eyewear to avoid skin and eye contact. Dispose of used oil and empty containers in accordance with local environmental regulations, and keep the product out of reach of children and unauthorized personnel.