



VELLON E40 5W40

PETROL ENGINE OIL-FULLY SYNTHETIC

DESCRIPTION

Elube Vellon E40 5W40 is a high-performance, fully synthetic multigrade motor oil formulated with 100% virgin base stock and advanced additives to meet the demanding requirements of modern gasoline and diesel engines. Suitable for Japanese, European, and Korean vehicles, it delivers outstanding protection, engine cleanliness, and reliable performance across a wide temperature range and diverse driving conditions.

INTERNATIONAL STANDARDS

- API SN

KEY FEATURES & BENIFITS

- **API SN Certified:** Ensures excellent piston cleanliness, wear protection and sludge control.
- **Fully Synthetic Formula:** Promotes superior engine cleanliness and thermal stability.
- **Thermal Stability:** Maintains performance at high temperatures reducing sludge and varnish.
- **Turbocharger Protection:** Suitable for turbocharged and naturally aspirated gasoline engines.
- **Extended Drain Intervals:** Long-lasting protection.

SPECIFICATIONS

Parameters	Unit	Test Method	Results
Appearance	-	Visual	C & B
Colour	-	ASTM D1500	L 2.5
Density at 15 °C	kg/m ³	ASTM D1298	852
Viscosity at 40 °C	CST	ASTM D445	80.1
Viscosity at 100 °C	CST	ASTM D445	13.2
Viscosity Index	-	ASTM D2270	168
Pour Point	°C	ASTM D97	-43
Flash Point	°C	ASTM D92	232

PACK SIZES

208 L

4X4 L

12X1 L

STORAGE & HANDLING

Store in a cool, dry, and well-ventilated area away from direct sunlight, heat, and ignition sources. Keep containers tightly closed to prevent contamination and use clean equipment when handling. Follow proper industrial hygiene practices, including the use of protective gloves and eyewear to avoid skin and eye contact. Dispose of used oil and empty containers in accordance with local environmental regulations, and keep the product out of reach of children and unauthorized personnel.