

PETROL ENGINE OIL

DESCRIPTION

Elube Vellon V50 20W50 is a high-performance multigrade engine oil for gasoline and diesel engines. Formulated with 100% virgin base oils and advanced additives, it ensures engine cleanliness and protection. Suitable for Japanese, European, and Korean vehicles, it performs reliably under varied conditions. Meets global standards, supporting extended engine life and improved fuel efficiency.

INTERNATIONAL STANDARDS

API SL/CF

KEY FEATURES & BENIFITS

- Wear Protection: Minimizes engine wear and extends life.
- Clean Engine: Controls sludge and deposit build-up.
- Thermal Stability: Maintains performance at high temperatures.
- Fuel Efficiency: Reduces friction and fuel consumption.
- Cold Start Lubrication: Ensures fast protection on startup.
- Rust & Corrosion Resistance: Shields internal parts in tough conditions.
- Low Oil Consumption: Reduces top-up frequency.

SPECIFICATIONS

Parameters	Unit	Test Method	Results
Appearance	-	Visual	C & B
Colour	-	ASTM D1500	L 2.5
Density at 15 °C	kg/m³	ASTM D1298	890
Viscosity at 40 °C	CST	ASTM D445	176.5
Viscosity at 100 °C	CST	ASTM D445	20
Viscosity Index	-	ASTM D2270	127
Pour Point	°C	ASTM D97	-26
Flash Point	°C	ASTM D92	237

PACK SIZES

208 L

4X4 L

12X1 L

STORAGE & HANDLING

Store in a cool, dry, and well-ventilated area away from direct sunlight, heat, and ignition sources. Keep containers tightly closed to prevent contamination and use clean equipment when handling. Follow proper industrial hygiene practices, including the use of protective gloves and eyewear to avoid skin and eye contact. Dispose of used oil and empty containers in accordance with local environmental regulations, and keep the product out of reach of children and unauthorized personnel.